

Polaris MV800 4x4



DIMENSIONS

Length	89 in / 226.0 cm
Width	48 in / 121.9 cm
Height	58 in / 147.3 cm
Ground Clearance	10.5 in / 26.7 cm
Dry Weight	1042 lb / 472.6 kg

CAPACITIES

Front Rack Capacity	200 lbs / 90.7 kg
Rear Rack Capacity	400 lbs / 181.4 kg
Towing Capacity	1500 lbs / 680.4 kg
Hitch Tongue Weight	150 lbs / 68.0 kg
Hitch	2 in / 5 cm Receiver

INSTRUMENTATION / FEATURES

Gauge Type	Analog / Digital
Speedometer / Odometer	Standard
Tachometer	Standard
Tripmeter	Standard
Hourmeter	Standard
High Beam Indicator	Standard
Gear Indicator	Standard
Fuel Gauge	Electronic
Warning Light	Hi Temp / Low Bat
DC Outlet	Standard
Black Out Drive	Standard
NATO Litter Rack Mount	Standard
Dual Fuel Tanks	Standard
IR Lights	Optional
Top Speed	58 MPH / 93.3 KPH
Heavy Duty Suspension	Standard
Full Underbody Skid Plate	Standard

ENGINE

Engine Type	Twin Cylinder 4-stroke
Displacement	760 cc; 40 HP
Cooling System	Liquid
Starting	Electric w/Recoil Back Up
Exhaust	Dual to Single Pipe

FUEL

Carburetor	Spark Ignited Direct Injection (SID)
Type Fuel	JP-8
Fuel Capacity	4.75 gal / 17.9 l (front) / 4 gal / 15.1 l (rear)

DRIVETRAIN

Transmission	Drumshift H/L/N/R/P
Drive System	Automatic PVT
Final Drive	On-Demand True All-Wheel Shaft Drive
Engine Braking (EBS)	Standard

BODY / SUSPENSION

Body Style	MV ATV
Front	MacPherson Strut w/ 8.2 in / 20.8 cm of travel
Rear	Independent w/ 9.5 in / 24.1 cm of travel

BRAKES / TIRES

Front Brake System	Single-Lever Dual Hydraulic Disc
Rear Brake System	Hydraulic Rear Foot Brake, Single Disc
Tires Front / Rear	25 x 8 -12 Run Flat Tires

AVAILABLE COLOR



For more information, please visit the Polaris Defense website www.polarisdefense.com or

Contact us at:

info@polarisdefense.com

Or call, 1-866-468-7783



POLARIS
DEFENSE