

MVRS700 6x6



DIMENSIONS

Length	110 in / 279 cm
Width	60 in / 152.4 cm
Height	75 in / 190.5 cm
Wheelbase	76 in / 193 cm
Ground Clearance	10 in / 25 cm
Dry Weight	1652 lbs / 750 kg
Turning Radius	148 in / 376 cm

CAPACITIES

Seating Capacity	2 Adults
Cargo Box Capacity	1200 lbs / 544.3 kg
Box Dimensions	66.5x55x10 in / 168.9 x139.7x25.4 cm
Vehicle Payload	1800lbs / 816.5 kg
Towing Capacity	1750 lbs / 793.8 kg
Hitch Tongue Weight	150 lbs. / 68.1 kg

INSTRUMENTATION / FEATURES

Speedometer	Standard
High Beam Indicator	Standard
Gear Indicator	Standard
Digital Fuel Gauge	Standard
Warning Light	Standard
DC Outlet	Standard - 3 outlets
Brake Light/Taillight	Standard
2-inch Receiver Hitch	Standard
Steel Cargo Box	Standard
Top Speed	42 MPH / 67.6 KPH
Full Underbody Skid Plate	Standard
Water Forging	30 in / 76.2 cm

OPTIONAL ACCESSORIES

In-Cab Weapons Storage	2876930
Hardcoat Poly Windshield	2876937
Steel Roof w/Integrated Handles	2876933
Spare Tire Holder	2876939
Fuel/Water Can Holder	2876936
Litter Rack Mount	2877217

ENGINE

Engine Type	Twin Cylinder, 4-Stroke
Displacement	683 cc / 40 HP
Lubrication	Pressurized Wet Sump
Cooling System	Liquid-cooled
Starting	Electrical
Exhaust	Canister Style U.S.F.S. Approved
Alternator	500 W

FUEL

Carburetor	EFI
Fuel Tank	13 gal. / 49.2 L
Fuel Delivery	Electric Fuel Pump
Type Fuel	Gas - 87 Octane or 89 Oxygenated

DRIVETRAIN

Transmission	In Line EZ Shift H/L/R/N
Drive System	Automatic PVT
Final Drive	On-Demand True 6-Wheel Shaft Drive

BODY / SUSPENSION

Body Style	MVRS 6x6
Front	MacPherson Strut
Center	Independent
Rear	Independent

BRAKES / TIRES

Brake System	Foot Operated 4-Wheel Hydraulic Disc
Parking Brake	Hand Lever Activated
Tires Front / Rear	25x8-12 / 25x11-12 Run Flat Tires

AVAILABLE COLOR



For more information, please visit the Polaris Defense website www.polarisdefense.com or Contact us at: info@polarisdefense.com Or call, 1-866-468-7783