

RANGER Crew



DIMENSIONS

Length	145 in / 368.3 cm
Width	60 in / 152.4 cm
Height	75 in / 190.5 cm
Wheelbase	108 in / 274.3 cm
Ground Clearance	11 in / 27.9 cm
Dry Weight	1460 lbs / 662.25 kg
Turning Radius	224 in / 568.9 cm

CAPACITIES

Seating Capacity	6 Adults
Cargo Box Capacity	1000 lbs. / 454 kg
Cargo Box Volume	13 ft ³ / .37 m ³
Vehicle Payload	1750 lbs / 794 kg
Towing Capacity	2000 lbs / 907.19 kg
Hitch Tongue Weight	150 lbs. / 68.1 kg

INSTRUMENTATION / FEATURES

Speedometer	Standard
High Beam Indicator	Standard
Gear Indicator	Standard
Digital Fuel Gauge	Standard
Warning Light	Standard
DC Outlet	Standard
Brake Light/Taillight	Standard
2-inch Receiver Hitch	Standard
Composite Cargo Box	Standard
Top Speed	44 MPH / 71 KPH
Full Underbody Skid Plate	Standard
Water Forging	30 in / 76.2 cm

OPTIONAL ACCESSORIES

Hardcoat Poly Windshield	2876193
Crew Soft Top and Rear Panel	2876815-070
Crew Side Enclosures	2876768-070
4.0 CI Warn Winch	2876667
Lock & Ride Cargo Box	2875056

ENGINE

Engine Type	Twin Cylinder, 4-Stroke
Displacement	683 cc / 40 HP
Lubrication	Pressurized Wet Sump
Cooling System	Liquid-cooled
Starting	Electrical
Exhaust	Canister Style U.S.F.S. Approved
Alternator	500 W

FUEL

Carburetor	EFI
Fuel Tank	9 gal. / 36 L
Fuel Delivery	Electric Fuel Pump
Type Fuel	87 Octane or 89 Oxygenated

DRIVETRAIN

Transmission	In Line EZ Shift H/L/R/N
Drive System	Automatic PVT
Final Drive	On-Demand True All Wheel Drive
Lockable Rear Differential	Standard / Electronic


BODY / SUSPENSION

Body Style	2008 RANGER Crew
Front	MacPherson Strut w/ 8 in. / 20.3 cm of travel
Rear	Independent w/ 9 in / 22.9 cm of travel

BRAKES / TIRES

Brake System	Foot Operated 4-wheel Hydraulic Disc
Parking Brake	Foot Actuated, Mechanical
Tires Front / Rear	26x8-12 / 26x11-12 PXT Radial

AVAILABLE COLORS



For more information, please visit the
Polaris Defense website www.polarisdefense.com or
Contact us at:
info@polarisdefense.com
Or call, 1-866-468-7783